

CAT. N° 6 781 37



## RCD SOCKET SYNERGY - 2 GANG - ELO - DOUBLE POLE 30 MA - 13 A 250 V~ - WHITE

Pack (number of units)	1
Volume (dm <sup>3</sup> )	0,883
Weight (g)	264,00

### Product characteristics

#### RCD sockets 13 A - 250 V~

- Conform to BS 7288: 1990 and BS 1363 - Part 2: 1995
- Conventional earth pin release shutter
- Maximum operating current 16 A
- Electronic RCD module with a membrane switch for "test and reset"
- Flush mounting back box : min. 25 mm deep

#### ELO - DP 30 mA

- Trips in the event of a power failure
- Ideal for applications where it is desirable to prevent automatic reactivation of equipment after a power failure
- For hazardous, e.g. machinery, power tools
- 2 gang
- Nominal plate dimensions: 86 x 146 mm

### General characteristics

#### Synergy™ - British standard RCD sockets - white

- Front plates: white thermoset
- Terminal screws captive and backed off ready for cabling - large angled terminal entries
- Compact mechanism for maximised wiring space
- Supplied with faceplate screw caps

### Documentation



#### Catalogue pages & additional information

- [Description page \(p.582\)](#)



#### Installation instructions & related documents

- [0064FU9-06](#)