

CAT. N° 8 320 32


**FUSED CONNECT UNIT SYNERGY -UNSWITCHED + CORD  
-13 A-250 V~ SLEEK DESIGN BRUSHED STAINLESS STEEL**

|                           |        |
|---------------------------|--------|
| Pack (number of units)    | 1      |
| Volume (dm <sup>3</sup> ) | 0,462  |
| Weight (g)                | 169,00 |

**Product characteristics**
**Fused connection units unswitched 13 A - 250 V~**

- Conform to BS 1363: Part. 4
- Front cable outlet with cord grip
- Fuses supplied
- Locked captive fuse carrier (padlockable)
- For flush-mounting, back box to be min. 35 mm deep
- Supplied with 1 gang side extension (3 mm thick) in case of extra wiring space needed
- Nominal plate dimensions: 86 x 86 mm

**Unswitched - with cord outlet**

- Brushed stainless steel

**General characteristics**
**Synergy™ - cooker control units, fused connection units and cable outlets - Sleek Design**

- Sleek design
- BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L
- PSS: Plates made of Stainless Steel + rust resistance
- GG: Plates made of Stainless Steel + rust resistance
- Terminal screws captive and backed off ready for cabling - large angled terminal entries
- Compact mechanism for maximum wiring space

**Documentation**
 **Catalogue pages & additional information**

- [Description page \(p.593\)](#)

 **Agreements & certificates of conformity**

- [ASTA - 880](#)

 **Installation & technical data**

- [F02656EN-00](#)