

CAT. N° 8 323 51



ROTARY UNIVERSAL DIMMER SYNERGY -1 GANG -2-WAY PUSH SLEEK DESIGN POLISHED STAINLESS STEEL

Pack (number of units)	1
Volume (dm ³)	0,677
Weight (g)	217,00

Product characteristics

**Push on/off rotary universal dimmers 5 W / 300 W 100 - 240 V~
- 50/60 Hz**

1 gang - 2-way push switches

- Conform to IEC 60669-2-1
- For flush-mounting back box to be min. 40 mm deep
- Equipped with overvoltage and short-circuit protection
- Screw terminals
- For all types of lamps:
 - dimmable LEDs: 5 W to 75 W
 - dimmable compact fluorescent lamps: 5 W to 75 W
 - halogen with ferromagnetic or electronic transformer: 5 VA to 300 VA
 - fluorescent tube - ballast: 5 VA to 300 VA
 - halogen and incandescent 230 V: 5 W to 300 W
- When switched on, gradually (2 seconds) lights up at the level set before last switch-off
- Nominal plate dimensions: 86 x 86 mm
- Polished stainless steel

General characteristics

**Synergy™ - single pole switches and dimmers -
Sleek Design**

- Sleek design
- BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L
- PSS: Plates made of Stainless Steel + rust resistance
- GG: Plates made of Stainless Steel + rust resistance
- Terminal screws captive and backed off ready for cabling - large angled terminal entries
- Compact mechanism for maximum wiring space

Documentation



Catalogue pages & additional information

- [Description page \(p.590\)](#)



Installation & technical data

- [F02305EN-00](#)



Installation instructions & related documents

- [LE08934AA_EN-AR](#)



Agreements & certificates of conformity

- [OC / CB - 210106146GZU-VOC001](#)
- [OC / CB - SE-104104](#)