

CAT. N° 8 330 32

**FUSED CONNECT UNIT SYNERGY -UNSWITCHED WITH
CORD OUTLET -AUTHENTIC BRUSHED STAINLESS STEEL**

Pack (number of units)	1
Volume (dm ³)	0,462
Weight (g)	143,00

Product characteristics**Fused connection units 13 A - 250 V~**


- Conform to BS 1363: Part. 4
- Front cable outlet with cord grip
- Fuse supplied
- Locked captive fuse carrier (padlockable)
- For flush-mounting, back box to be min. 25 mm deep

Unswitched with cord outlet

- Nominal plate dimensions: 86 x 86 mm
- Brushed stainless steel

General characteristics**Synergy™ - cooker control units and fused
connection units - Authentic**

- Slim front plate:
 - BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L
 - PSS: Plates made of Stainless Steel + rust resistance
 - GG: Plates made of Stainless Steel + rust resistance
- Terminal screws captive and backed off ready for cabling - large angled terminal entries
- Compact mechanism for maximum wiring space

Documentation **Catalogue pages & additional information**

- [Description page \(p.589\)](#)

 **Agreements & certificates of conformity**

- [ASTA - 880](#)

 **Installation & technical data**

- [F02655EN-00](#)