



Product: [4102UE](#)

Security & Sound, 4 Conductor 14 AWG BC, LSZH

Product Description

Security & Commercial Audio Cable, 4-14 AWG stranded (19x27) bare copper conductors with polyolefin insulation, FRNC/LSZH jacket with ripcord.

Technical Specifications

Product Overview

Suitable Applications:	Intercom/PA systems, Sound/Audio Systems
------------------------	--

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter
14	19x27	BC - Bare Copper	1.8 mm

Conductor Count:	4
------------------	---

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance
PP - Polypropylene	2.34 mm	0.05 mm

Color Chart

Number	Color
Wire 1	Black
Wire 2	White
Wire 3	Red
Wire 4	Green

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
LSZH - Low Smoke Zero Halogen (Flame Retardant)	6.8 mm	0.4 mm	Provided under the sheath

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
8.3 Ohm/km

Capacitance

Nom. Capacitance Conductor to Conductor
75 pF/m

Current

Max. Recommended Current [A]
8 A

Temperature Range

Storage Temp Range:	-30°C To +70°C
---------------------	----------------

Supplied by Digitalstout.com UAE

Operating Temp Range:	-20°C To +70°C
Other Temp Range:	-20-+70 °C

Mechanical Characteristics

Max. Pull Tension:	60 N
Min Bend Radius (W/o Pulling Strength):	34 mm
Min Setting Radius:	68 mm

Standards

CPR Euroclass:	Eca
----------------	-----

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Eca
EU RoHS Compliance Date (yyyy-mm-dd):	2015-09-30

Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
IEC 60754-1 - Halogen Amount:	Zero
IEC 61034-2 - Smoke Density Min. Transmittance:	60%

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
4102UE.00305	Gray, RAL 7032	Reel	305 m	8719605006264
4102UE.01300	Orange	Reel	300 m	8719605192479

History

Update and Revision:	Revision Number: 0.136 Revision Date: 05-04-2021
----------------------	--

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.