

# Product: 5001UE Security & Sound, 3 Conductor 12 AWG BC, Riser **Product Description** Security & Commercial Audio Cable, 3 Conductor 12 AWG stranded (19x25) bare copper conductors with polyolefin insulation, Riser, PVC jacket with ripcord. **Technical Specifications Product Overview** Suitable Applications: Intercom/PA Systems, Sound/Audio Systems **Physical Characteristics (Overall)** Conductor AWG No. of Conductors Stranding Material 12 19x25 BC - Bare Copper 3 Conductor Count: 3 Insulation Material Nominal Wall Thickness PP - Polypropylene 0.011 in Color Chart Number Colo Black 1 2 White 3 Red Outer Shield Material Material No Shield Outer Jacket Material Material Nominal Diameter Nominal Wall Thickness Ripcord PVC - Polyvinyl Chloride 0.277 in 0.017 in Yes **Construction and Dimensions** Cabling Twists 2.526 twist/ft **Electrical Characteristics**

Conductor DCR

Nominal Conductor DCR

1.6 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor

24 pF/ft

#### Current

Max. Recommended Current [A]
12 Amps per Conductor at 25°C

#### Voltage

UL Voltage Rating 300 V RMS

#### **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

## **Mechanical Characteristics**

Bulk Cable Weight:	78.5 lbs/1000ft
Max. Pull Tension:	228 lbs
Min Bend Radius/Minor Axis:	2.8 in
Standards	•
NEC Articles:	Article 725
NEC/(UL) Compliance:	CL3R

## Applicable Environmental and Other Programs

Environmental Space:	Indoor - Riser	
EU Directive 2000/53/EC (ELV):	Yes	
EU Directive 2003/96/EC (BFR):	Yes	
EU Directive 2011/65/EU (RoHS 2):	Yes	
EU Directive 2012/19/EU (WEEE):	Yes	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	<ul> <li>لا المراجع المراجع</li> </ul>
EU CE Mark:	Yes	
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01	
MII Order #39 (China RoHS):	Yes	
Flammability, LS0H, Toxicity Te	esting	
UL Flammability:	UL1666 Vertical Riser	
CSA Flammability:	FT4	
UL voltage rating:	300 V RMS	Char and the second sec
Plenum/Non-Plenum		
Plenum (Y/N):	No	
Plenum Number:	6001UE	
Part Number		
Variants		
Item # Color Putup Type	ength UPC	
5001UE 0081000 Gray Reel 1,	000 ft 612825155706	
Footnote:	C - CRATE REEL PUT-UP.	
History		
Update and Revision:	Revision Number: 0.273 Revision Date: 03-16-2021	· · · · · · · · · · · · · · · · · · ·
© 0004 Daldan Jua		

### Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1666 Vertical Riser
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6001UE

### Part Number

#### Variants

Item #		Color	Putup Type	Length	UPC
5001UE 0081	000	Gray	Reel	1,000 ft	612825155706
Footnote:	Footnote:			C - C	RATE REEL PUT

#### History

#### © 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and

Supplied by Digitalstout.com UAR