

RCCB 4P 40A 300mA AC

CFC441J

Architecture

Similar Comments		
Services.		
19		
rekoneki		FZEJAE
10 0 0		~//
3 18 N		1 Dr.
		. 🗸 '
		4.
		17
		< V
		,
	(A)	-)
	Architecture	
	Neutral position	right
	Number of poles	4 P
	Fixing mode	Din-Rail
	Controls and indicators	
	Ground fault signalisation	no
	With fault indicator	yes
	With fault indicator	yes
	Main electrical features	
	Main electrical features	
	Frequency	50 Hz
,	Electric current	
. 49	Rated residual operating current	300 mA
	Withstand not tripping on 8-20 ?s wave	0,25 kA
	Breaking and opening capacity	1500 A
	Rated conditional short-circuit current Inc according	6 kA
En	to EN 61008-1	O KA
70,	10 214 01000 1	
SUPPlied by Dis	Electric current / temperature	
~6.	Rating current -15°C	40 A
	Rating current -20°C	40 A
5	Rating current 0°C	40 A
	Rating current 10°C	40 A
	Rating current -10°C	40 A
	Rating current 15°C	40 A
	Rating current 20°C	40 A
	Rating current 25°C	40 A
	Rating current -25°C	40 A
	Rating current 30°C	40 A
	Rating current 35°C	40 A
	Rating current 40°C	40 A
	Rating current 45°C	40 A
	Rating current 5°C	40 A
	Rating current -5°C	40 A
	Rating current 50°C	40 A
	Rating current 55°C	40 A
	Rating current 60°C	40 A



Technical Properties	
Rating current 65°C	40 A
Rating current 70°C	40 A
Power	
Power loss per pole at In	3,6 W
Total power loss under IN	8,1 W
Tripping	
Short-time delayed tripping	no
Protected against nuisance tripping	no
Endurance	16)
Electric endurance in number of cycles	2000
Number of mechanical operations	4000
Dimensions	(9)
Depth of installed product	70 mm
Height of installed product	83 mm
Width of installed product	70 mm
Construction size (DIN 43880)	1
Installation, mounting	
Type of bottom rail clip for modular devices	plastic
Type of top rail clip for modular devices	NA
Bottom removability for modular devices	yes
Top removability for modular devices	no
Connection	
Type of connection	with screw
Standards	
Standard text	IEC 61008-1
European directive WEEE	not concerned
Safety	
Protection index IP	IP20
Residual current type	AC
Use conditions	
Degree of pollution according to IEC 60664 / IEC	2
60947-2	
60947-2 Altitude Storage temperature	2000 m -55 to 70 °C