



Series connection time switch 24 hrs., series connection time switch, 1 TLE



Part no. TSSD1NO
Catalog No. 167389
Alternate Catalog No. TSSD1NO

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	0
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	0
Static heat dissipation, non-current-dependent	P_{vs}	W	0.9
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	50
			0

Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Analogous time switch for distribution board (EC002304)		
Electric engineering, automation, process control engineering / Measurement technology, process measurement technology / Measuring appliance, time / Analogous time switch (ecI@ss10.0.1-27-20-01-09 [ACN651011])		
Mounting method		DIN rail
Number of channels		1
Supply voltage	V	230 - 230
Voltage type of supply voltage		AC
Frequency supply voltage	Hz	50 - 50
Autonomy in hours		0
Autonomy in years		0
Accuracy per day	s	0
60 min. program		No
24 h program		Yes
Weekly program		No
Annual program		No
Mains synchronous		Yes
Quartz controlled		Yes
Contact type		Normally open contact
Shortest switching time channel 1	min	15
Shortest switching time channel 2	min	0
Program shift divide 1	min	15
Program shift divide 2	min	0
Automatic switching summer-/winter time		No
Manual operation		Yes
Switching preselection		Yes
Nominal switching current at 250 V AC	A	16
Potential free switch contact		Yes
Degree of protection (IP)		IP20
Width in number of modular spacings		1
Width	mm	17.5
Height	mm	90
Depth	mm	65.5

Supplied by Digital Stout Innovation & Trading FZE UAE