

ET 16



Approvals



General Data

Type	ET 16
Wire Termination Technology	Screw Clamp
Ratings	16 sq mm/1.2 Nm
GTIN / Harmonize Custom Code	85389000
Standard Packing Qty (in No)	50
Country of Origin	India
Screw Size	M4

Dimensions & Weight

Height (mm)	52
Height (inches)	2.05
Width (mm)	45
Width (inches)	1.77
Thickness (mm)	12.5
Weight For Standard Packing Qty (Kg)	2.00

Material Data

Housing	PA 6,6
Standard Colour	Green-Yellow
Other Color Variants	No more colors available

Rated Conductor Size

Stranded Wire - min (sq mm)	6
Stranded Wire - max (sq mm)	16
Solid Wire - min (sq mm)	6
Solid Wire - max (sq mm)	25

Ratings - IEC

Standard	IEC 60947-7-2
Rated Voltage (V)	-
Rated Current (A)	-
Rated Cross Section (sq mm)	16
Short Time Withstand Current (kA)	1.92
Rated Impulse Withstand Voltage(kV)	-
Pollution Degree	III

Ratings-ATEX

Certificate No	-
Rated Current (A)	-
Rated Cross Section (sq mm)	16

Ratings-CSA

Rated Voltage (V)	-
Rated Current (A)	-
Wire Cross Section - min (AWG)	12

Wire Cross Section - max (AWG)

3

Ratings-uL

Rated Voltage (V)

-

Rated Current (A)

-

Conductor Size - min (AWG)

12

Conductor Size - max (AWG)

3

Accessories

Partition Plate With Foot

KBZF

Height : 65 mm

Width : 65 mm

Thickness : 1.50 mm



Protection Cover

PCK3

Height : 28 mm

Width : 58.35 mm

Thickness : 1 mm




End Clamp

SCUDD

Height : 50 mm

Width : 55.50 mm

Thickness : 10 mm




CHKS (Perforated)

Height : 7.5 mm

Width : 35 mm

Thickness : 1 mm



CHS

Height : 15 mm

Width : 32 mm

Thickness : 1.50 mm



Support for Protection Cover

UHDD

Height : 74.50 mm

Width : 55.82 mm

Thickness : 1.50 mm



Group Marking Holder

GMH 10

Height : 51 mm

Width : 41.50 mm

Thickness : 10 mm



GMH 20

Height : 51 mm

Width : 41.50 mm

Thickness : 20 mm



Note : Technical specifications may change in line with technical advances and industry standards