

**IP66 32A 2P ISOLATOR**

Technische Merkmale

**Architecture**

Type of order	Short thumb-grip
Type of case	in housing
Number of poles	2 P
Type of pole	1P+N

**Functions**

Reversing switch	no
Version as emergency stop installation	no
Version as main switch	yes
Version as safety switch	yes
Version as maintenance-/service switch	yes

**Controls and indicators**

Motor drive integrated	no
------------------------	----

**Main electrical features**

Rated operational voltage Ue	250 V
------------------------------	-------

**Voltage**

Rated insulation voltage	440 V
Rated impulse withstand voltage	4000 V

**Electric current**

Rated operational current in AC21	32 A
Rated operational current in AC21 category A	32 A
Acceptable current rating with AC22 category A	32 A
Rated operational current in AC23 category A	32 A
Rated short-circuit making capacity I <sub>cm</sub> under 240V AC according IEC 60947-3	384 A
Rated short-time withstand current I <sub>cw</sub>	384 A
Rated short-time withstand current I <sub>cw</sub> t=1s 220-240 V AC according IEC 60947-3	384 A

**Power**

Rated operation power at AC-23, 400 V	5,2 kW
---------------------------------------	--------

**Cover, door**

Interlockable	yes
---------------	-----

**Materials**

Toggle colour	Grey
---------------	------

**Dimensions**

Depth of installed product	87 mm
Height of installed product	170 mm
Width of installed product	84 mm

**Installation, mounting**

Tightening torque	2,5Nm
Suitable for front mounting	no
Suitable for front mounting center	no
Suitable for ground mounting	yes
Suitable for intermediate mounting	no
Suitable for distribution board installation	no

**Connection**

Connection cross-sect. rigid cable	6 / 10 mm <sup>2</sup>
Type of connection	with screw

**Equipment**

With optional voltage release	no
Motor drive optional	no

**Standards**

Standard text	IEC 60947-3
---------------	-------------

**Safety**

Protection index IP	IP66
---------------------	------

Supplied by Digital Stout Innovation &amp; Trading FZE UAE