

Euro Multimedia Modules

TV CO-AXIAL OUTLETS
FOR DIGITAL TV
SCREENED
NON ISOLATED

AUDIO & HD



K5850WHI K5850BLK



K5851WHI K5851BLK



K5855WHI K5855BLK



K5852WHI



K5852DABWHI



K5853WHI



K5853DABWHI



K5854DABWHI



K5807WHI



K5805WHI



K5806WHI



K5809WHI



K5809BLK

K5850WHI **5**
K5850BLK **5**
SINGLE OUTLET (IEC MALE)
ONE MODULE 25 X 50MM

K5851WHI **5**
K5851BLK **5**
SINGLE OUTLET (IEC FEMALE)
ONE MODULE 25 X 50MM

K5855WHI **5**
K5855BLK **5**
SINGLE F-TYPE SATELLITE SOCKET
ONE MODULE 25 X 50MM

Fully screened non isolated TV outlets containing a combination of single, TV/FM Diplexer and TV/FM/SAT Triplexer for use within digital TV systems and interactive TV services. Single outlets for connection to a single TV, FM or Satellite co-axial aerial lead.

MOUNTING BOXES:
Min box depth 32mm

DIMENSIONS:
1 Module 25 x 50mm
2 Module 50 x 50mm

BS 3041: 1997
IEC 169-2: 1965
BS EN 50083 & BS 5733: 2010
where applicable

These products are fully compatible with Labgear TV distribution systems and are approved for use in "Sky Homes" and "Homes On" specifications

K5852WHI **5**
K5852BLK **5**
TWIN OUTLET
TV/FM DIPLEXER
TWO MODULE 50 X 50MM
(IRELAND ONLY)

K5852DABWHI **5**
K5852DABBLK **5**
TWIN OUTLET TV-FM/DAB DIPLEXER
TWO MODULE 50 X 50MM

K5853WHI **5**
K5853BLK **5**
TRIPLE OUTLET
TV/FM/SATELLITE TRIPLEXER
TWO MODULE 50 X 50MM
(IRELAND ONLY)

TV/FM diplexer units for connection to a single co-axial aerial lead with combined TV and FM signals.
TV/FM/SAT triplexer units for connection to a single co-axial aerial lead with combined TV, FM and Satellite signals

PERFORMANCE
SINGLE OUTLETS
TV/FM IEC MALE OR FEMALE
DC-950MHz
SAT F-TYPE
DC-1.75GHz

TV/FM/SAT PRODUCTS
OUTLET TV
DIPLEXER
5-65MHz
470-862MHz
87.5-108MHz
N/A

FM/DAB
SAT

TV/FM/DAB/SAT PRODUCTS FOR DIGITAL RADIO
OUTLET TV
DIPLEXER
5-65MHz
470-862MHz
87.5-230MHz
N/A

FM/DAB
SAT OR SAT1
SAT2

K5853DABWHI **5**
K5853DABBLK **5**
TRIPLE OUTLET TV-FM/DAB-SAT
TRIPLEXER TWO MODULE 50 X 50MM

K5854DABWHI **5**
K5854DABBLK **5**
QUAD OUTLET TV-FM/DAB-2XSAT
TWO MODULE 50 X 50MM

K5807WHI **5**
K5807BLK **5**
FEMALE HDMI OUTLET

K5807 Female HDMI Outlet is HDMI 1.1, 1.2 and 1.3 compatible, HDCP compliant.
Data Rate: Up to 2.25 Gbps
Scan: Up to 1080p/1920x1200
Input Connector:
1 x HDMI Female (Type A)
Output Connector:
1 x HDMI Female (Type A)
Supports high resolution input:
PC: VGA, SVGA,
SXVGA (1280x1024) and UXGA (1600x1200, 1920x1200)
HDTV: 480p, 720p, 1080i and 1080p
HDMI input cable should be no larger than 20m.
Weight of product: 16g
Dimensions: 50 x 50 x 20mm

OUTLET TV
FM
SAT1

TRIPLEXER
5-65MHz
470-862MHz
87.5-108MHz
950-2300MHz

OUTLET TV
FM
SAT1
SAT2

TRIPLEXER
5-65MHz
470-862MHz
87.5-230MHz
950-2300MHz
5-2300MHz

K5805WHI **5**
K5805BLK **5**
AUDIO BINDING POST SET
FOR SINGLE LOUD SPEAKER

K5806WHI **5**
K5806BLK **5**
RCA TO SCREW TERMINATION SET
1 RED AND 1 BLACK

K5809WHI **5**
K5809BLK **5**
TRIPLE RCA TO SCREW
TERMINATION SET
1 YELLOW, 1 WHITE, 1 RED

WEIGHT: 23g
DIMENSIONS:
50 x 25 x 28mm