

## KUT 2.5



### Approvals



### General Data

Type	KUT 2.5
Wire Termination Technology	Screw Clamp
Ratings	800 V/24 A/2.5 sq mm/0.5 Nm
GTIN / Harmonize Custom Code	85389000
Standard Packing Qty (in No)	100
Country of Origin	India
Screw Size	M3

### Dimensions & Weight

Height (mm)	41
Height (inches)	1.60
Width (mm)	42.50
Width (inches)	1.67 Inc
Thickness (mm)	6
Weight For Standard Packing Qty (Kg)	0.88

## Material Data

Housing	PA 6,6
Standard Colour	Grey
Other Color Variants	Black, Blue, Green, Grey, Khakhi, Red, Yellow

## Rated Conductor Size

Stranded Wire - min (sq mm)	0.5
Stranded Wire - max (sq mm)	2.5
Solid Wire - min (sq mm)	0.5
Solid Wire - max (sq mm)	4

## Ratings - IEC

Standard	IEC 60947-7-1
Rated Voltage (V)	800
Rated Current (A)	24
Rated Cross Section (sq mm)	2.5
Short Time Withstand Current (kA)	0.48
Rated Impulse Withstand Voltage(kV)	8
Pollution Degree	III

## Ratings-ATEX

Certificate No	400
Rated Current (A)	20
Rated Cross Section (sq mm)	2.5

## Ratings-CSA

Rated Voltage (V)	600
Rated Current (A)	25
Wire Cross Section - min (AWG)	20

Wire Cross Section - max (AWG)

12

## Ratings-uL

Rated Voltage (V)

600

Rated Current (A)

25

Conductor Size - min (AWG)

20

Conductor Size - max (AWG)

12

## Accessories

### End Plate

**KPNS**

Height : 31 mm

Width : 36.50 mm

Thickness : 1.50 mm



### Partition Plate Without Foot

**KBM**

Height : 37.50 mm

Width : 50.50 mm

Thickness : 1.50 mm



### Partition Plate With Foot

**KBXF**

Height : 53.4 mm

Width : 54 mm

Thickness : 1.5 mm



### Protection Cover




**SCUN (Universal Rail Mounted)**

**Height : 35.50 mm**

**Width : 50.60 mm**

**Thickness : 9.50 mm**




**SCUSL**

**Height : 41 mm**

**Width : 47.50 mm**

**Thickness : 8 mm**



**Cross Connection Link Assembly**

**CCLK2.5**


**( 2W, 3W, 4W, 5W, 10W )**



**Comb-type Shorting Link**

**SLC4N**

**( 2 Way, 3 Way, 4 Way, 5 Way, 10 Way )**



**Marking Label**

**LABEL KN5.5**

