

Audio Control & Instrumentation Cable, 2C to 8C, 14AWG, Unscreened & PVC Sheath




C1002, C1004, C1006, C1249, C1251, C4876

Applications

Unscreened Multi-Conductor cable suitable for Audio, Control, Instrumentation and Building Management Systems (BMS). UL listed E486876.

Cross Section Drawing



Design

Unit	Properties
Conductor	N x Bare Copper wire, 14AWG flexible
Insulation	Polyolefin Core 1: Black Core 2: White Core 3: Red Core 4: Green Core 5: Brown Core 6: Blue Core 7: Orange Core 8: Yellow
Rip cord	Nylon yarn
Sheath	Flame-Retardant Polyvinyl Chloride (PVC) Standard colour: Grey
Standard Put Up Length	305 meters

*Other Colors, Put Up Lengths and structures can be manufactured upon request, please contact your local B3 International sales representative.

Audio Control & Instrumentation Cable, 2C to 8C, 14AWG, Unscreened & PVC Sheath



C1002, C1004, C1006, C1249, C1251, C4876

Physical Characteristics

Part Number	C1002	C1004	C1006	C1249	C1251	C4876
No of cores x 14AWG (19 x 27)	2	3	4	6	8	9
Nom. Diameter Conductor(mm)	1.8					
Nom. Radial Thickness Insulation(mm)	0.3					
Nom. Radial Thickness Sheath(mm)	0.4					
Nom. Overall Diameter(mm)	5.6	6.0	6.6	8.0	8.7	9.7
Operating Temperature (°C)	-25 to +75					
Max. Recommended Pulling Tension (N)	420	635	845	1265	1685	1895
Min. Bend Radius (install)(mm)	58	64	68	84	87	97
Nominal Cable Weight (kg/km)	43	64	84	126	168	182

Electrical Characteristics at 20°C

Part Number	C1002	C1004	C1006	C1249	C1251	C4876
No of cores x 14AWG (19 x 27)	2	3	4	6	8	9
Max. DC Resistance Conductor (Ω/km)	9.36					
Capacitance conductor to conductor (pF/m)	51	55	55	50	50	50
Nominal Inductance (μH/m)	0.5					
Max. Recommended Current at 25°C (Amps)	8	6.4	6.4	5.6	5.6	5.6
Max. Operating Voltage (Vrms)	300					

Reference Standards

(BS) EN 50290-2
IEC 60228
IEC 60332-1
RoHS directives