

RAMCRO - DATA LAN - M-BUS Cable
For standard applications, flame retardant.

Single pair, PVC-Insulation, UnScreened, PVC-Sheath

MSE0105HBAAN-T-RB

Application

M-BUS (Meter-Bus) is a european standard (EN 13757-2) physical and Ink layer, EN 13757-3 application layer) for the remote reading of gas or electricity meters. M-Bus is also suitable for other types of consumption meters.


Construction

Formation	1 Pair	Unit	Nominal Value
Section	18 AWG		
Conductor	Tinned copper wire, 7 strand	mm	1,1
Insulation	Polyethylene - PE	mm	1,7
Colour Code	Black, White		
Individual Screen	N.A.		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	N.A.		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	Polyvinyl chloride - PVC - Grey RAL 7001	mm	4,8
Cable Printing	RAMCRO ITALY R1203 DATA LAN CABLE 1PR 22AWG UNSCREENED 300 V 75 C IEC 60332-1/UL 1581 - MSE0105HBAAN-T-RB - "PROD.WEEK/18" + BATCH + METER MARKING		

Technical Data & Standard References

Fire Propagation:		Type of Cable:	DATA LAN - M-BUS Cable
- Test on single cable	IEC 60332-1	Low Voltage Directive	2014/35/UE
- Test on bunched cables	IEC 60332-3	Other References:	
Limiting Oxygen Index (LOI)	(min 30%)		
Smoke Density	IEC 61034		
Amount of halogen acid gas	IEC 60754-1 (max 15%)		
Acidity (ph value) and conductivity	IEC 60754-2		
Sunlight resistance	UL 1581 section 1200		
Notes			

Electrical & Mechanical Data

Conductor Cross-section	Nom.	18 AWG	Temperature Range:		
DC Resistance per core at 20° C	max	Ω/km	23,2	During Operation	° C -30°C up to 80°C
Insulation Resistance at 20° C	min	MΩ*km	5000	During Installation	° C -30°C up to 80°C
Nominal Mutual Capacitance		pF/ft	18.24		
Inductance	max	mH/km	1	Min. Bending Radius	mm 8 x cable diameter
Test Voltage - Core/Core	V	2000		Max Pulling Tension	N/mm2 43
Test Voltage - Core/Screen	V	2000		Weight Approx	kg/km 33
				Standard Put Up Length	ft 1000
Operating Voltage	V	300			