



Product: 5100FE ☑

Security & Sound, 2 Conductor 14 AWG BC, Shielded, CL3R, FPLR

# **Product Description**

Security & Commercial Audio Cable, Riser-CL3R-FPLR, 2-14 AWG stranded bare copper conductors with polypropylene insulation, Beldfoil® shield and PVC jacket with ripcord

# **Technical Specifications**



Element	Nom. Conductor D	CR Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Oth	er (Conds + Shield)	Max. Current
Conductor(s)	2.54 Ohm/1000ft	54 pF/ft	97.25 pF/ft		8 Amps per conductor @ 25°C
Nom Outer Sh	nield DCR: 1	0 Ohm/1000ft			
Voltage					1
UL Voltage F	Rating				
300 V (CL3R,	FPLR)				*
Mechanica	I Characteristic	<b>`</b>			
Miconamo	ii Onaraotoriotic				
Temperature					
UL Rating	Operating				
75°C -2	20°C to +75°C				•
Bend Radius					·
Stationary M	in. Installation Min.	1			

## Voltage

## **Mechanical Characteristics**

## Temperature

<b>UL Rating</b>	Operating	
75°C	-20°C to +75°C	

## Bend Radius

2.23 111 2.2 111	
Max. Pull Tension:	125 lbs
Bulk Cable Weight:	37 lbs/1000ft

#### Standards and Compliance

2.25 in 2.2 in

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Fire Resistance:	UL1666 Riser, IEC 60332-1-2
NEC / UL Compliance:	Article 725, Article 760, CL3R, FPLR
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6100FH

# **History**

Update and Revision:	Revision Number: 0.349 Revision Date: 03-16-2021

#### © 2021 Belden, Inc

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

