



Product: 6502FE

Security & Alarm Cable, Plenum-CMP, 4-22 AWG stranded bare copper conductors with Flamarrest® insulation, Beldfoil® shield and Flamarrest® jacket with ripcord

Product Description

Security & Sound Cable, Plenum-CMP, 4-22 AWG stranded bare copper conductors with Flamarrest® insulation, Beldfoil® shield and Flamarrest® jacket with ripcord

Technical Specifications

Suitable Applications: Sec			ecurity System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy Environment						
Constructi	on Details								
Conductor									
Element	No. of Elements	Size	Stranding	Mat	erial				
Conductor(s)	4	22 AWG	7x30	BC - Bar	re Copper				
Insulation									
Element	Material		Nom. Thickr	ness No	m. Insulation Diameter	Color Code			
Conductor(s)	PVC - Polyvinyl C	hloride 0	.009 in (0.23	mm) 0.0	47 in (1.2 mm)	Black, Red, White, Green			
Outer Shield									
Shield Type	Material			Drainwire					
Таре	Bi-Laminate (Alum	+Poly) 1	100% 2	4 AWG (7	x32) TC				
Outer Jacket									
Mater	ial Nom.	Thicknes	s Nom.	Diameter	Ripcord				
PVC - Polyvin	yl Chloride 0.015 i	in (0.38 m	m) 0.147 in	(3.73 mm) Yes				
Overall Cable	Diameter (Nominal): 0.147	in (3.73 mm)						
Electrical (Characteristic	•							
Electricals									
Element	Nom. Conductor	DCR No	om. Capacit	ance Con	d-to-Cond Nom. Capa	citance Cond-to-Other (Co	nds + Shield)	Max. Current	
Conductor(s)	16.2 Ohm/1000ft	33	.0 pF/ft (108	pF/m)	59 pF/ft (19) pF/m)		2.2 Amps per Conductor at 25°C	

300 V (CMP)

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	0°C to +75°C

Bend Radius

 Stationary Min.
 Installation Min.

 1.47 in (37.3 mm)
 1.47 in (37.3 mm)

Max. Pull Tension:	42 lbs (19 kg)	
Bulk Cable Weight:	17 lbs/1000ft	

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum), FT6
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	СМР
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	5502FE

History

Update and Revision:

Revision Number: 0.474 Revision Date: 04-03-2023

Part Numbers

Variants

ltem #	Color	UPC	Footnote
6502FE 8771000	Natural	612825177609	С
6502FE 877500	Natural	612825177616	
6502FE 877C500	Natural		
6502FE 877U1000	Natural	612825177593	
6502FE 0071000	Violet	612825377726	
6502FE 0071000	Violet	612825377726	
6502FE 007U1000	Violet	612825377832	
6502FE 007U1000	Violet	612825377832	

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.