CAT. N° 6 846 20

SOCKET OUTLET PLEXO 66 - 1 GANG UNSWITCHED - OPAQUE LID - 13 A 250 V~ - GREY

Pack (number of units)	1
Volume (dm³)	1,563
Weight (g)	280,00

Product characteristics

13 A - 250 V~ socket outlets

- Conform to BS 1363: Part 2
- Fitted with rear gasket with groove to deposit silicone
- 1 gang
- Unswitched socket with opaque lid

General characteristics

Plexo™ 66 complete surface-mounting - IP 66 - IK 08

- Grey RAL 7016/TO 29
- Supplied with ISO 20 membrane glands and caps for rear cabling
- For top or down cabling, plastic cable glands have to be used
- Stainless steel captive terminal screws supplied in backed-off position

Documentation

Catalogue pages & additional information

- Description page (p.609)

Installation & technical data

- F00127EN-01

Installation instructions & related documents

- 0064ER4-01

Agreements & certificates of conformity

- OC / CB - FR_710379

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.