

CAT. N° 7 300 37



FUSED CONNECTION UNIT SYNERGY - DOUBLE POLE SWITCHED + INDICATOR - WHITE

Pack (number of units)	10
Volume (dm³)	4,055
Weight (g)	1 242,00

Product characteristics

Fused connection units 13 A - 250 V~

- Conform to BS 1363: Part 4
- Fused 13 A (fuse supplied)
- Front cable outlet with cord grip
- Locked captive fuse carrier (padlockable)
- For flush-mounting, back box to be min. 25 mm deep
- Nominal plate dimensions: 86 x 86 mm

Double pole switched

- \blacksquare With red LED power indicator and cord outlet
- LED invisible until activated

General characteristics

Synergy $^{\text{\tiny TM}}$ - cooker control units, fused connection units and cable outlets - white

- Front plates: white thermoset
- Terminal screws captive and backed off ready for cabling large angled terminal entries
- Compact mechanism for maximised wiring space
- Supplied with faceplate screw caps

Documentation

- Catalogue pages & additional information
 - Description page (p.583)
- Magreements & certificates of conformity
 - <u>ASTA 880</u>

- Installation & technical data
 - F00285EN-00
- Environmental product profile
 - Environnemental product sheet n°A E2450A-EN

^{*} All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis: before-tax price list, May 2018