

CAT. N° 7 311 51



ROTARY DIMMER SYNERGY - 1 GANG - 5 W/ 300 W- 100/240 V~ - 50/60 HZ - WHITE

Pack (number of units)	1
Volume (dm ³)	0,602
Weight (g)	185,00

Product characteristics

Push on/off rotary universal dimmer 5 W/300 W 100 - 240 V~ - 50/60 Hz

- Conform to IEC 60669-2-1
- For flush-mounting back box to be min. 40 mm deep
- Equipped with overvoltage and short-circuit protection
- Screw terminals
- For all types of lamps:
 - dimmable LEDs: 5 W to 75 W
 - dimmable compact fluorescent lamps: 5 W to 75 W
 - halogen with ferromagnetic or electronic transformer: 5 VA to 300 VA
 - fluorescent tube - ballast: 5 VA to 300 VA
 - halogen and incandescent 230 V: 5 W to 300 W
- When switched on, gradually (2 seconds) lights up at the level set before last switch-off
- Nominal plate dimensions: 86 x 86 mm
- 1 gang
- Can be associated with an active power compensator

General characteristics

Synergy™ - single pole switches, single pole push and key switches, rotary dimmers - white

- Front plates: white thermoset
- Terminal screws captive and backed off ready for cabling - large angled terminal entries
- Compact mechanism for maximised wiring space
- Supplied with faceplate screw caps

Documentation



Catalogue pages & additional information

- [Description page \(p.579\)](#)



Agreements & certificates of conformity

- [OC / CB - 210106146GZU-VOC001](#)
- [OC / CB - SE-103189](#)
- [OC / CB - SE-104104](#)