CAT. N° 8 321 50

ROTARY DIMMER SYNERGY - 1 GANG - 2 WAY PUSH SWITCH - SLEEK DESIGN BRUSHED STAINLESS STEEL

Pack (number of units)	1
Volume (dm³)	0,462
Weight (g)	244,00

Product characteristics

Push on/off rotary dimmers 1000 W - 250 V~ - 50/60 Hz

- Conform to BS EN 60669-1
- For flush-mounting back box to be min. 40 mm deep
- 60-1000 W (230 V)
- 60-500 W (127 V) for incandescent and halogen lamps 60-600 VA (230 V)
- 60-300 VA (127 V) for halogen lamps with electronic transformers 60-100 VA (230 V)
- 60-500 VA (127 V) for halogen lamps with ferromagnetic transformers
- Nominal plate dimensions: 86 x 86 mm

1 gang - 2-way push switches

- Brushed stainless steel

General characteristics

Synergy™ - single pole switches and dimmers - Sleek Design

- Sleek design
- BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L
- PSS: Plates made of Stainless Steel + rust resistance
- GG: Plates made of Stainless Steel + rust resistance
- Terminal screws captive and backed off ready for cabling - large angled terminal entries
- Compact mechanism for maximum wiring space

Documentation

Catalogue pages & additional information

- Description page (p.590)

Installation & technical data

- F02307EN-00

Installation instructions & related documents

- LE08889AA

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.