

CAT. N° 8 330 33



FUSED CONNECT UNIT SYNERGY -UNSWITCH + CORD OUTLET + LED -AUTHENTIC BRUSHED STAINLESS STEEL

Pack (number of units)	1
Volume (dm³)	0,462
Weight (g)	143,00

Product characteristics

Fused connection units 13 A - 250 V~

- Conform to BS 1363: Part. 4
- Front cable outlet with cord grip
- Fuse supplied
- Locked captive fuse carrier (padlockable)
- For flush-mounting, back box to be min. 25 mm deep

Unswitched with blue LED power indicator + cord outlet

- Nominal plate dimensions: 86 x 86 mm
- Brushed stainless steel

General characteristics

Synergy™ - cooker control units and fused connection units - Authentic

- Slim front plate:
- BSS: Plates made of austenitic Stainless Steel non-magnetic grade 304 L
- PSS: Plates made of Stainless Steel + rust resistance
- GG: Plates made of Stainless Steel + rust resistance
- \blacksquare Terminal screws captive and backed off ready for cabling large angled terminal entries
- \blacksquare Compact mechanism for maximum wiring space

Documentation

- Catalogue pages & additional information
 - Description page (p.589)
- Magreements & certificates of conformity
 - <u>ASTA 880</u>

Installation & technical data
■ F02655EN-00

^{*} All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis: before-tax price list, May 2018