



**Product:** <u>1523A</u> ☑

Broadband Coax, Series 11, 14 AWG Solid BCCS, Foil + 60% AL Braid, PVC Jkt, CM

# **Product Description**

Broadband Coax, Series 11, 14 AWG Solid Bare Copper Covered Steel Conductor, PE Insulation, Foil + 60% Aluminum Braid Shield, PVC Jacket, CM

## **Technical Specifications**

# **Product Overview**

Suitable Applications:	Broadband, Cable Television (CATV), RF drop cable, Over-The-Air (OTA) antennas

# **Construction Details**

Const	ruction Details	s	-0/						
Series 7	Туре:	11							
onduct	tor								
WG	Stranding Nom. D	Diameter Material							
4	Solid 0.064 in	n BCCS - Bare Copper Co	overed Steel	10					
sulatio	on				12		C/X		
		Nom. Diameter			63				
E - Po	olyethylene (Foam)	0.280 in			9				
						0.			
	hield Material					JX.			
	Outer Shield Type Tape	Material Tri-Laminate (Alum+Poly+Alum)	Material Trade Name	Coverage					
	Braid	Aluminum	Duobona® II	60%					
	2.4.4	7 44111114111		0070			YX.		
uter Ja	acket Material								
	Material N	Nom. Diameter					* (		
PVC - F	Polyvinyl Chloride 0	0.393 in							
lectri	ical Characteri	istics						4	
	Tour Gridian doctors								
eturn L	Loss (RL)								
Freque	ncy [MHz] Min. St	tructural Return Loss [dB]							
5 - 1000	0 MHz 20 dB								
ttenuat	tion								CAM
Freque	ency Max. Attentua	ation [dB/100ft]							
5 MHz	0.38 dB/100ft								
55 MHz	0.96 dB/100ft								
211 MH	1.90 dB/100ft								
250 MH	lz 2.05 dB/100ft								

#### Conductor

AWG	Stranding	Nom. Diameter	Material
14	Solid	0.064 in	BCCS - Bare Copper Covered Steel

## Insulation

Material	Nom. Diameter
PE - Polyethylene (Foam)	0.280 in

#### **Outer Shield Material**

Layer	Outer Shield Type	Material	Material Trade Name	Coverage
1	Таре	Tri-Laminate (Alum+Poly+Alum)	Duobond® II	100%
2	Braid	Aluminum		60%

## **Outer Jacket Material**

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.393 in

# **Electrical Characteristics**

# Return Loss (RL)

Frequency [MHz]	Min. Structural Return Loss [dB]
5 - 1000 MHz	20 dB

#### Attenuation

Frequency	Max. Attentuation [dB/100ft]
5 MHz	0.38 dB/100ft
55 MHz	0.96 dB/100ft
211 MHz	1.90 dB/100ft
250 MHz	2.05 dB/100ft
270 MHz	2.13 dB/100ft
300 MHz	2.25 dB/100ft
330 MHz	2.35 dB/100ft
350 MHz	2.42 dB/100ft
400 MHz	2.60 dB/100ft
450 MHz	2.75 dB/100ft

500 MHz	2.90 dB/100ft
550 MHz	3.04 dB/100ft
600 MHz	3.18 dB/100ft
750 MHz	3.65 dB/100ft
870 MHz	4.06 dB/100ft
1000 MHz	4.35 dB/100ft

#### Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Impedence	Nom. Velocity
12 Ohm/1000ft	4.1 Ohm/1000ft	16.3 pF/ft	75 Ohm	83%

#### Voltage

UL Voltage Rating

## **Mechanical Characteristics**

#### Temperature

UL Rating	Operating
75°C	-40°C to +75°C

#### **Bend Radius**

# Installation Min.

Bulk Cable Weight: 56 lbs/1000ft

Max. Pull Tension: 199 lbs

### **Standards and Compliance**

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor, Sunlight Resistance
Sustainability:	CA Prop 65
Flammability / Fire Resistance:	UL1685 UL Loading
NEC / UL Compliance:	CM, CATV
CEC / C(UL) Compliance:	CM
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	ANSI/SCTE 74
Plenum Number:	1523AP

# **History**

Update and Revision: Revision Number: 0.370 Revision Date: 03-16-2021

## © 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.