



Product: <u>5202UE</u> ☑

Security & Sound, #16-4c, BC, CMR

# **Product Description**

Security & Sound Cable, Riser-CMR, 4-16 AWG stranded bare copper conductors with polypropylene insulation, PVC jacket with ripcord

### **Technical Specifications**

## **Product Overview**

Suitable Applications:	Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls

#### **Construction Details**

#### Conductor

Element	Number of Element	AWG	Stranding	Material
Conductor(s)	4	16	19x29	BC - Bare Copper

#### Insulation

Element	Material	Thickness	Color Code
Conductor(s)	PP - Polypropylene	0.008 in	Black, Red, White, Green

### **Outer Jacket Material**

	Material	Thicknes	s Nom. Diameter	Ripcord
PV	/C - Polyvinyl Chloride	0.017 in	0.210 in	Yes
Ca	able Diameter (Nominal	l): 0.2	210 in	

### **Electrical Characteristics**

### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Conductor(s)	4.2 Ohm/1000ft	23 pF/ft	5.0 Amps per conductor @ 25°C

## Voltage



## **Mechanical Characteristics**

## Temperature

UL Rating	Operating
75°C	-20°C to +75°C

# Bend Radius

Stationary Min.	Installation Min
2 in	2.1 in
Max. Pull Tensio	n:
Bulk Cable Weig	ht:

## **Standards and Compliance**

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Fire Resistance:	UL1666 Riser, FT4, IEC 60332-1-2
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6202UE

#### **History**

Update and Revision:	Revision Number: 0.274 Revision Date: 03-16-2021

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. en.
1 gene.
on Regu.