

Part Number: 5302FE



Security & Sound, #18-4c, BC, Shielded, CMR

Product Description

Security & Sound Cable, Riser-CMR, 4-18 AWG stranded bare copper conductors with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

Technical Specifications

Physical Characteristics (Overall)

Conductor						
ANNO COMPANIENT MARKET TO THE COMPANIENT OF THE						
AWG Stranding Material No. of	Conductors					
18 7x26 BC - Bare Copper 4						
Conductor Count:		4	ı			
Conductor Size:		1	8 AWG			
nsulation						
Material Nominal Wall Thickness						
PP - Polypropylene 0.008 in						
Color Chart	0					
Color						
Red						
White						
Green						
Outer Shield Material						
Type Material	Material Trade Name	Coverage [%] Di	rainwire Material	Drainwire AWG	Drainwire Construction n x D	
Tape Aluminum Foil-Polyester Tape w/Shortin	ng Beldfoil®	100 % TO	C - Tinned Copper	24	7x32	
PVC - Polyvinyl Chloride 0.188 in Construction and Dimensions	0.017 in Ye	es	6			
Cabling				1		
Lay Length Lay Direction Twists						
3 in Left Hand 4 twist/ft				6	•	
Electrical Characteristics				4	/X	
Conductor DCR					**	•
Nominal Conductor DCR Nominal Outer Sh	nield DCR					
6.5 Ohm/1000ft 7.2 Ohm/1000ft					UA	
Capacitance					1	•
Nom. Capacitance Conductor to Conductor		tor to Other Conduc	ctor to Shield			
	48.5 pF/ft					
27 pF/ft Shielding:			oil(s) or Copper Ta			

Nominal Conductor DCR	Nominal Outer Shield DCI		
6.5 Ohm/1000ft	7.2 Ohm/1000ft		

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield		
27 pF/ft	48.5 pF/ft		

Current

Element	Max. Recommended Current [A]			
10C Temperature Rise	4 Amps per conductor @ 25°C A			

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	30 lbs/1000ft
Max Recommended Pulling Tension:	103.6 lbs
Min Bend Radius/Minor Axis:	1.8 in

Standards

NEC Articles:	800
NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR);	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	7/	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	Y		UL1666 Riser
CSA Flammability:		4	FT4

Plenum/Non-Plenum

Plenum Number:			6302FE
Part Number			
/ariants			
ltem #	Color	Footnote	
5302FE.00152	Chrome		
5302FE.00305	Chrome		YX
5302FE.00U305	Chrome		
5302FE 0081000	Gray	С	
5302FE 008500	Gray		
5302FE 008C250	Gray		
5302FE 008U1000	Gray		
5302FE 008U500	Gray		
Footnote:			C - CRATE REEL PUT-UP.

Part Number

Variants

Item #	Color	Footnote
5302FE.00152	Chrome	
5302FE.00305	Chrome	
5302FE.00U305	Chrome	
5302FE 0081000	Gray	С
5302FE 008500	Gray	
5302FE 008C250	Gray	
5302FE 008U1000	Gray	
5302FE 008U500	Gray	

© 2018 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

