



Product: <u>5304FE</u> ☑

Security & Sound, #18-6c, BC, Shielded, CMR

# **Product Description**

Security & Sound Cable, Riser-CMR, 6-18 AWG stranded bare copper conductors with polypropylene insulation, Beldfoil® shield and PVC jacket with ripcord

#### **Technical Specifications**

### **Product Overview**

Suitable Applications: Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy Environment

#### **Construction Details**

#### Conductor

Element	Number of Element	AWG	Stranding	Material
Conductor(s)	6	18	7x26	BC - Bare Copper

#### Insulation

Element	Material	Thickness	Color Code
Conductor(s)	PP - Polypropylene	0.009 in	Black, Red, White, Green, Brown, Blue

### **Outer Shield Material**

Shield Type	Material	Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC

#### Outer Jacket Material

Material		Thickr	ness	Nom. Diameter	Ripcord
	PVC - Polyvinyl Chloride	0.017 in 0.:		0.224 in	Yes
Cable Diameter (Nominal):		):	0.22	4 in	

## **Electrical Characteristics**

#### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	6.5 Ohm/1000ft	27 pF/ft	48.5 pF/ft	3.5 Amps per conductor @ 25°C
Nom Outer Sh	nield DCR: 15.2	5 Ohm/1000ft		

#### Voltage

UL Voltage Rating 300 V (CMR)

## **Mechanical Characteristics**

#### Temperature

<b>UL Rating</b>	Operating
75°C	-20°C to +75°C

### Bend Radius

Stationary Min.	Installation Min.
2.25 in	2.2 in

Max. Pull Tension:	148 lbs
Bulk Cable Weight:	43 lbs/1000ft

#### **Standards and Compliance**

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Fire Resistance:	UL1666 Riser, IEC 60332-1-2
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6304FE

#### **History**

Update and Revision:	Revision Number: 0.256 Revision Date: 03-16-2021

#### © 2021 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all apple able envilonmental programs as listed in the data of the product selection to mental transcense a part of The Product and the data of the product selection to entit at becomes a part of The Product Disclosure is not to be considered a warranty or qualify specification. Regulatory information is 6 eguatory and product selection to entit at becomes a part of The Product Disclosure is not to be considered a warranty or qualify specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulation to their individual usage of the product.