



Product: <u>5504UE</u> ☑

Security & Sound, #22-6c BC, CMR

# **Product Description**

Security & Sound Cable, Riser-CMR, 6-22 AWG stranded bare copper conductors with polypropylene insulation, PVC jacket with ripcord

# **Technical Specifications**

## **Product Overview**

Suitable Applications:	Security System, Intercom/PA, Au	udio/Speaker, Power-Limited Controls

#### **Construction Details**

#### Conductor

Element	Number of Element	AWG	Stranding	Material
Conductor(s)	6	22	7x30	BC - Bare Copper

#### Insulation

Element	Material	Thickness	Color Code
Conductor(s)	PP - Polypropylene	0.008 in	Black, Red, White, Green, Brown, Blue

## **Outer Jacket Material**

Material	Thickness	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.017 in	0.168 in	Yes
Cable Diameter (Nominal): 0.1		168 in	

### **Electrical Characteristics**

### Electricals

Conductor(s)	6	22 7	7x30	BC - Bare Copper		
Insulation						
Element	Material	Thicknes	ss	Color Code	X	
Conductor(s)	PP - Polypropylene	0.008 in	Black, R	Red, White, Green,	Brown, Blue	
Outer Jacket I	Material					
Mater	ial Thicknes	s Nom.	Diameter	Ripcord		<b>'0</b> 'x
PVC - Polyvin	yl Chloride 0.017 in	0.168 i	in	Yes		
Cable Diamet	er (Nominal):	).168 in				
Electrical (	Characteristics					
Electricals						
Element	Nom. Conductor DCR	Nom.	Capacitan	ce Cond-to-Cond	Max. Current	
Conductor(s)	16.2 Ohm/1000ft	17 pF.	/ft		2 Amps per conductor @ 25°C	
Voltage	Vellere					
UL Voltage R	ating					
UL Voltage Rating 300 V (CMR)  Mechanical Characteristics						
Mechanical Characteristics						
Temperature						
UL Rating	Operating					•
75°C -2	20°C to +75°C					

### Voltage



# **Mechanical Characteristics**

#### Temperature

<b>UL Rating</b>	Operating
75°C	-20°C to +75°C

#### Bend Radius

Stationary Min.	Installation Min.
1.625 in	1.7 in
Max. Pull Tension:	
Bulk Cable Weigh	ht:

## **Standards and Compliance**

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Fire Resistance:	UL1666 Riser, FT4, IEC 60332-1-2
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark
Plenum Number:	6504UE

### **History**

Update and Revision:	Revision Number: 0.266 Revision Date: 03-16-2021

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

nda.
all applica.
High specification.
product. Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.