

RAMCRO BMS - Audio, Control & Instrumentation Cable MULTI CONDUCTOR CABLE

LSZH(FRNC) sheathed, screened cable with 16 AWG conductors

Code: SAS0203HXEDH-RB

Application

LSZH - FRNC sheathed multi-conductor cables are suitable for Building Management Systems (BMS), Sound, Audio, Security, Safety, Control and Instrumentation.


Construction

| Parameter | Description | Unit | Nominal Value |
|-------------------|--|------|---------------|
| Formation | 2 Cores | | |
| Section | 16 AWG | | |
| Conductor | Plain annealed copper wire, Multistrand | mm | 1,5 |
| Insulation | Polyolephine | mm | 1,9 |
| Colour Code | Black, Red | | |
| Individual Screen | N.A. | | |
| Wrapping | at least 1 layer of plastic tape 0,023 mm | | |
| Collective Screen | 0,026 mm Aluminium / PETP tape over tinned copper drain wire | | |
| Inner Sheath | N.A. | | |
| Armour | N.A. | | |
| Outer Sheath | Thermoplastic Low Smoke, Halogen Free - LSZH (FRNC) - Purple RAL 4005 | mm | 4,7 |
| Cable Printing | RAMCRO MADE IN ITALY R1711 AUDIO CONTROL & INSTRUMENTATION CABLE 2C 16AWG SCREENED LSZH (FRNC) 300 V 75 C IEC 60332-1/UL 1581 - SAS0203HXEDH-RB - "PROD.WEEK/18" + BATCH + METER MARKING | | |

Technical Data & Standard References

| | | | |
|---|----------------------|-----------------------|--|
| Fire Propagation: | | Type of Cable: | Audio, Control & Instrumentation Cable |
| - Test on single cable | IEC 60332-1 | Low Voltage Directive | 2014/35/UE |
| - Test on bunched cables | IEC 60332-3 | Other References: | |
| Smoke Density | IEC 61034 | | |
| Amount of Halogen acc. to IEC 60754-1 & EN50267-1 | ZERO | | |
| Acidity (ph value) and conductivity | IEC 60754-2 | | |
| Sunlight resistance | UL 1581 section 1200 | | |
| Notes | | | |

Electrical & Mechanical Data

| | | | | | |
|---------------------------------|------|--------|--------------------|---|-----------------------|
| Conductor Cross-section | Nom. | 16 AWG | Temperature Range: |  | |
| DC Resistance per core at 20° C | max | Ω/km | 15,47 | During Operation | ° C -30°C up to 80°C |
| Insulation Resistance at 20° C | min | MΩ*km | 25 | During Installation | ° C -30°C up to 80°C |
| Nominal Mutual Capacitance | max | pF/m | 170 | Min. Bending Radius | mm 8 x cable diameter |
| Inductance | max | mH/km | 1 | Max Pulling Tension | N/mm2 116 |
| Test Voltage - Core/Core | V | 2000 | Weight Approx | kg/km 39 | |
| Test Voltage - Core/Screen | V | 2000 | Put up length | mt 305 | |
| Operating Voltage | V | 300 | | | |

Issued by: RAMCRO S.p.A.



Date of issue:

Prepared by RAMCRO Tech

Via Marzorati, 15 - 20014 Nerviano - Milan - Italy / www.ramcro.it

18/09/2018 00:00

Creator: LDG

Transfer to third parties only under authorization by Ramcro S.p.A.

Empty Form

Printing errors excepted. Subject to alterations.