


TECHNICAL DATA SHEET

1 kV, 4 C x 185 Cu (Cl2)/XLPE/PVC/SWA/PVC



D.REF : 203

REF : STD TDS_0_ID 61

Product Standard

BS 5467

Performace Standard (Flame / Fire - Test)

IEC 60332 - 1

Rated voltage (Uo/U) (Um)

0.6/1 (1.2) kV

1 Sectoral Stranded Copper Class : 2 Conductor

Number of Core(s)	4	Nos
Nominal cross sectional area	185	mm ²
Approx. Diameter of Conductor	Sectoral	mm

2 Insulation - XLPE

Color (s)	Red, Yellow, Blue, Black,
Nominal Thickness	1.6mm
Approx. Diameter over Insulation	Sectoralmm

3 4 Core Laid up with Non Hygroscopic PP Yarn Fillers and Followed by Binder Tape

Approx. Diameter over Laid Up	43.4	mm
-------------------------------	------	----

4 Extruded Bedding - PVC

Nominal Thickness	1.4	mm
Approx. Diameter over bedding	45.7	mm

5 Armor - Type: Steel Wire

Nominal Diameter of wire	2.5	mm
Approx. Diameter over armour	50.6	mm

TECHNICAL DATA SHEET



1 kV, 4 C x 185 Cu (Cl2)/XLPE/PVC/SWA/PVC

6 Extruded Outer Sheath - PVC (Black)

Nominal Thickness	2.6	mm
Approx. Diameter over outer sheath	54.9	mm
7 Approx. Weight of complete cable	9769	kg / km

8 Electrical Parameters

Max. DC Resistance of Conductor at 20°C	0.0991	Ω/km
Approx. AC Resistance of Conductor at Maximum Operating Temperature	0.129	Ω/km
Approx. Capacitance	0.58	μF / km
Approx. Inductance	0.23	mH / km
Approx. Inductive Reactance	0.073	Ω/km
Approx. Impedance	0.15	Ω/km
Approx. Voltage Drop	0.26	mV/Amp/mt

9 CURRENT CARRYING CAPACITY based on the conditions specified

Installation Type (Single Circuit)	3 core	
Soil Thermal Resistivity	1.2	°C.m/W
Ground temperature	15	°C
Ambient air temperature	30	°C
Burial depth	500	mm
Laid in ground	460	Amps
Laid in Duct	380	Amps
In air	463	Amps

10 Maximum conductor temperature for continuous operation / Short Circuit Operation

90/250 °C

11 Short Circuit Current carrying capacity for 1 second, cable loaded as above prior to short circuit for

Conductor	26.455	kA/ 1 sec
-----------	--------	-----------

12 Installation Parameters

Maximum pulling force (For Conductor)	2000	kgf
Minimum Bending Radius	440	mm

**Drawing not to Scale*

**All dimensions and weight mentioned are approximate.*

Refer " **Ducab Drum Handling, Storing and Installation Guide " for more details on Drum Handling.*

**This TDS is Auto-Generated from Design Data Base, Hence no signature is required.*