



ESC340

Contactor 40A, 3NO, 230V

Technische Merkmale

Architecture

| | |
|-----------------|----------------|
| Type of order | Not applicable |
| Number of poles | 3 P |

Main electrical features

| | |
|------------------------------|-------|
| Frequency | 50 Hz |
| Rated operational voltage Ue | 400 V |

Voltage

| | |
|---------------------------------|-------|
| Rated insulation voltage | 440 V |
| Command voltage AC | 230 V |
| Rated impulse withstand voltage | 4 kV |

Electric current

| | |
|---|------|
| Acceptable current load with AC7 category A | 40 A |
| Acceptable current load with AC7 category B | 25 A |
| Thermal rated current outside of housings | 40 A |

Power

| | |
|---|---------|
| Inrush power absorbed | 62,5 W |
| Operating consumption | 5,75 W |
| Contact rating with 230 V in AC7 category A | 7,3 kW |
| Contact rating with 230 V in AC7 category B | 2,6 kW |
| Contact rating with 400 V in AC7 category A | 22 kW |
| Contact rating with 400 V in AC7 category B | 7,8 kW |
| Power loss per contact | 3,2 W |
| Total power loss under IN | 15,35 W |
| Power dissipation per coil | 0,5 W |

Tripping

| | |
|-------------------------------|-------|
| Time of response when closing | 25 ms |
| Time of response when opening | 20 ms |

Resistance

| | |
|--------------------|-------|
| Winding resistance | 770 Ω |
|--------------------|-------|

Endurance

| | |
|--|---------|
| Electric endurance in number of cycles | 30000 |
| Number of mechanical operations | 1000000 |

Dimensions

| | |
|-----------------------------|-------|
| Depth of installed product | 60 mm |
| Height of installed product | 85 mm |
| Width of installed product | 54 mm |

Fluorescent bulbs control

| | |
|--|---------|
| Max. load fluorescent lamp | 1900 VA |
| Max. power with fluorescent parallel lamps | 1300 VA |
| Fluorescent lamps in duo circuit | 3000 VA |

Incandescent bulbs control

| | |
|------------------------------------|--------|
| Max. power with incandescent lamps | 4000 W |
|------------------------------------|--------|

Installation, mounting

| | |
|-------------------|---------------------------|
| Tightening torque | Coil: 2,5Nm, Power: 3,5Nm |
|-------------------|---------------------------|

Connection

| | |
|---|-------------------------|
| Max cable connect. cross section (flexible) for control | 1 to 6 mm ² |
| Connection cross-section of the control cable solid | 1 to 10 mm ² |
| Connection cross-sect. rigid cable | 4 / 25mm ² |
| Connection cross-sect. flexible conductor | 4 / 16mm ² |
| Type of connection | with screw |
| Number of contacts | 3 |
| Type of contacts | 3NO |

Equipment

| | |
|---------------------|-----|
| Can be accessorized | yes |
|---------------------|-----|

Use

| | |
|--------------------------------|----|
| Local operation/hand operation | no |
|--------------------------------|----|

Standards

| | |
|-------------------------|-----------|
| European directive WEEE | concerned |
|-------------------------|-----------|

Safety

| | |
|---------------------|---------------|
| Protection class | isol.class II |
| Protection index IP | 2 |

Use conditions

| | |
|---------------------|--------------|
| Storage temperature | -40 to 80 °C |
|---------------------|--------------|

Identification

| | |
|---------------|-----|
| Device family | ESC |
|---------------|-----|