



MCN300

MCB 3P 6kA C-0.5A 3M

Architecture	
Neutral position	without neutral
Number of protected poles	3
Number of poles	3 P
Type of pole	3 P
Fixing mode	Din-Rail
Curve	C
Controls and indicators	
With fault indicator	no
Connectivity	
Bottom connection alignment for modular devices	Aligned terminal
Top connection alignment for modular devices	Aligned terminal
Main electrical features	
Frequency	50/60 Hz
Rated short circuit breaking capacity Icn AC according 6 kA IEC60898-1	
Type of supply voltage	AC
Rated operational voltage Ue	415 V
Voltage	
Rated insulation voltage	500 V
Rated impulse withstand voltage	4000 V
Electric current	
Rated short circuit breaking capacity Icn under 400V 6 kA AC according IEC60898-1	
Rated service breaking capacity Ics AC according IEC 60898-1 6 kA	
Magnetic regulating current at 40° C	5/10 In
min/maxi threshold value of the AC thermal operation 1,13/1,45 In	

Electric current / temperature

Rating current -15°C	0,62 A
Rating current -20°C	0,64 A
Rating current 0°C	0,58 A
Rating current 10°C	0,54 A
Rating current -10°C	0,6 A
Rating current 15°C	0,53 A
Rating current 20°C	0,51 A
Rating current 25°C	0,5 A
Rating current -25°C	0,66 A
Rating current 30°C	0,5 A
Rating current 35°C	0,46 A
Rating current 40°C	0,45 A
Rating current 45°C	0,43 A
Rating current 5°C	0,56 A
Rating current -5°C	0,59 A
Rating current 50°C	0,4 A
Rating current 55°C	0,4 A
Rating current 60°C	0,38 A
Rating current 65°C	0,37 A
Rating current 70°C	0,35 A

Current correction factors

Correction factor of magnetic tripping with 100 Hz	1,1
Correction factor of magnetic tripping with 200 Hz	1,2
Correction factor of magnetic tripping with 400 Hz	1,5
Correction factor of magnetic tripping with 60 Hz	1
Correction factor of rating current for 2 devices placed 1 side-by-side	
Correction factor of rating current for 3 devices placed 0,8 side-by-side	
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,7
Correction factor of rating current for 6 devices placed 0,6 side-by-side	

Power

Power loss per pole at I _n	1,15 W
Total power loss under I _N	3,42 W

Endurance

Electric endurance in number of cycles	4000
Number of mechanical operations	20000

Dimensions

Depth of installed product	70 mm
Height of installed product	84,6 mm
Width of installed product	52,5 mm

Installation, mounting

Type of top connection for modular devices	with screw
Tightening torque	2,8Nm
Type of bottom rail clip for modular devices	plastic
Type of top rail clip for modular devices	NA
Type of Bottom Connection for modular devices	Blconnect
Bottom removability for modular devices	yes

Technical Properties

Top removability for modular devices	no
--------------------------------------	----

Connection

Connection cross-sect. rigid cable	1 / 35mm ²
Connection cross-sect. flexible conductor	1 / 25mm ²
Type of connection	with screw
Connection cross section of access and exit with screws, for flexible conductor	1/25 mm ²
Connection cross-section of input and output with screws, for massive conductors	1/35 mm ²

Equipment

Quick connect	no
---------------	----

Standards

Standard text	IEC 60898-1
European directive WEEE	not concerned

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Operating temperature	-25 70 °C
Class of energy limitation I ² t	3
Altitude	2000 m
Storage temperature	-25 to 80 °C
Air humidity protection	for all climates
Storage/transport temperature	-25 80 °C