

RAMCRO - BMS-PVC-BC-Screened Cable

For standard applications, flame retardant.

Multicore, PP-Insulation, Collective Screened, PVC-Sheath

SAS0201HBAXH-RB

Application

PVC sheathed multi-conductor cables are suitable for Building Management Systems (BMS), Sound, Audio, Security, Safety, Control and Instrumentation.

Construction

| Formation | 2 Cores | Unit | Nominal Value |
|-------------------|--|------|---------------|
| Section | 14 AWG | | |
| Conductor | Plain annealed copper wire, Multistrand | mm | 1,8 |
| Insulation | Polypropylene - PP | mm | 2,3 |
| Colour Code | Black, Red | | |
| Individual Screen | N.A. | | |
| Wrapping | at least 1 layer of plastic tape 0,023 mm | | |
| Collective Screen | 0,026 mm Aluminium / PETP tape over tinned copper drain wire | | |
| Inner Sheath | N.A. | | |
| Armour | N.A. | | |
| Outer Sheath | Polyvinyl chloride - PVC - Grey RAL 7001 | mm | 5,9 |
| Cable Printing | RAMCRO ITALY R1001 AUDIO CONTROL & INSTRUMENTATION CABLE 2C 14AWG SCREENED PVC 300 V 75 C IEC 60332-1/UL 1581 - SAS0201HBAXH-RB - "PROD.WEEK/18" + BATCH + METER MARKING | | |

Technical Data & Standard References

| | | | |
|-------------------------------------|-----------------------|-----------------------|---------------------------|
| Fire Propagation: | | Type of Cable: | BMS-PVC-BC-Screened Cable |
| - Test on single cable | IEC 60332-1 | Low Voltage Directive | 2014/35/UE |
| - Test on bunched cables | IEC 60332-3 | Other References: | |
| Limiting Oxygen Index (LOI) | (min 30%) | | |
| Smoke Density | IEC 61034 | | |
| Amount of halogen acid gas | IEC 60754-1 (max 15%) | | |
| Acidity (ph value) and conductivity | IEC 60754-2 | | |
| Sunlight resistance | UL 1581 section 1200 | | |
| Notes | | | |

Electrical & Mechanical Data

| | | | | |
|---------------------------------|-------------------|--------|---------------------|-----------------------|
| Conductor Cross-section | Nom. | 14 AWG | Temperature Range: | |
| DC Resistance per core at 20° C | max Ω /km | 9,36 | During Operation | ° C -30°C up to 80°C |
| Insulation Resistance at 20° C | min $M\Omega$ *km | 1000 | During Installation | ° C -30°C up to 80°C |
| Nominal Mutual Capacitance | max pF/m | 105 | | |
| Inductance | max mH/km | 1 | Min. Bending Radius | mm 8 x cable diameter |
| Test Voltage - Core/Core | V | 2000 | Max Pulling Tension | N/mm2 193 |
| Test Voltage - Core/Screen | V | 2000 | Weight Approx | kg/km 65 |
| Operating Voltage | V | 300 | Put up length | mt 305 |

