

## RAMCRO - BMS-PVC-BC-UnScreened Cable

For standard applications, flame retardant.

Multicore, PP-Insulation, UnScreened, PVC-Sheath

SSS0201HBAXH-RB

### Application

PVC sheathed multi-conductor cables are suitable for Building Management Systems (BMS), Sound, Audio, Security, Safety, Control and Instrumentation.

### Construction

		Unit	Nominal Value
Formation	2 Cores		
Section	14 AWG		
Conductor	Plain annealed copper wire, Multistrand	mm	1,8
Insulation	Polypropylene - PP	mm	2,3
Colour Code	Black, Red		
Individual Screen	N.A.		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	N.A.		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	Polyvinyl chloride - PVC - Grey RAL 7001	mm	5,7
Cable Printing	RAMCRO ITALY R1002 AUDIO CONTROL & INSTRUMENTATION CABLE 2C 14AWG UNSCREENED PVC 300 V 75 C IEC 60332-1/UL 1581 - SSS0201HBAXH-RB - "PROD.WEEK/18" + BATCH + METER MARKING		

### Technical Data & Standard References

Fire Propagation:			
- Test on single cable	IEC 60332-1		
- Test on bunched cables	IEC 60332-3		
Limiting Oxygen Index (LOI)	(min 30%)		
Smoke Density	IEC 61034		
Amount of halogen acid gas	IEC 60754-1 (max 15%)		
Acidity (ph value) and conductivity	IEC 60754-2		
Sunlight resistance	UL 1581 section 1200		
Notes			
Type of Cable:	BMS-PVC-BC-UnScreened Cable		
Low Voltage Directive	2014/35/UE		
Other References:			

### Electrical & Mechanical Data

Conductor Cross-section	Nom.	14 AWG	Temperature Range:		
DC Resistance per core at 20° C	max	Ω/km	9,36	During Operation	° C -30°C up to 80°C
Insulation Resistance at 20° C	min	MΩ*km	1000	During Installation	° C -30°C up to 80°C
Nominal Mutual Capacitance	max	pF/m	51		
Inductance	max	mH/km	1	Min. Bending Radius	mm 8 x cable diameter
Test Voltage - Core/Core	V		2000	Max Pulling Tension	N/mm2 193
Test Voltage - Core/Screen	V		N.A.	Weight Approx	kg/km 56
Operating Voltage	V		300	Put up length	mt 305

