

### RAMCRO - BMS-PVC-BC-UnScreened Cable

For standard applications, flame retardant.

Multicore, PP-Insulation, UnScreened, PVC-Sheath

SSS0803HBAXX-RB

#### Application

PVC sheathed multi-conductor cables are suitable for Building Management Systems (BMS), Sound, Audio, Security, Safety, Control and Instrumentation.


#### Construction

		Unit	Nominal Value
Formation	8 Cores		
Section	16 AWG		
Conductor	Plain annealed copper wire, Multistrand	mm	1,5
Insulation	Polypropylene - PP	mm	1,9
Colour Code	Black, Red, White, Green, Brown, Blue, Orange, Yellow		
Individual Screen	N.A.		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	N.A.		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	Polyvinyl chloride - PVC - Grey RAL 7001	mm	7,1
Cable Printing	RAMCRO ITALY R1255 AUDIO CONTROL & INSTRUMENTATION CABLE 8C 16AWG UNSCREENED PVC 300 V 75 C IEC 60332-1/UL 1581 - SSS0803HBAXX-RB - "PROD.WEEK/18" + BATCH + METER MARKING		

#### Technical Data & Standard References

Fire Propagation:		Type of Cable:	BMS-PVC-BC-UnScreened Cable
- Test on single cable	IEC 60332-1	Low Voltage Directive	2014/35/UE
- Test on bunched cables	IEC 60332-3	Other References:	
Limiting Oxygen Index (LOI)	(min 30%)		
Smoke Density	IEC 61034		
Amount of halogen acid gas	IEC 60754-1 (max 15%)		
Acidity (ph value) and conductivity	IEC 60754-2		
Sunlight resistance	UL 1581 section 1200		
Notes			

#### Electrical & Mechanical Data

Conductor Cross-section	Nom.	16 AWG	Temperature Range:		
DC Resistance per core at 20° C	max	Ω/km	15,47	During Operation	° C -30°C up to 80°C
Insulation Resistance at 20° C	min	MΩ*km	1000	During Installation	° C -30°C up to 80°C
Nominal Mutual Capacitance	max	pF/m	45		
Inductance	max	mH/km	1	Min. Bending Radius	mm 8 x cable diameter
Test Voltage - Core/Core	V		2000	Max Pulling Tension	N/mm2 462
Test Voltage - Core/Screen	V		N.A.	Weight Approx	kg/km 122
Operating Voltage	V		300	Put up length	mt 305

Issued by: RAMCRO S.p.A.



Date of issue:

Prepared by RAMCRO Tech

Via Marzorati, 15 - 20014 Nerviano - Milan - Italy / www.ramcro.it

24/01/2019 00:00

Creator: LDG

Transfer to third parties only under authorization by Ramcro S.p.A.

Empty Form

Printing errors excepted. Subject to alterations.